



DESCRIPTION



Beak Ceiling Point emits a focused, defined beam of direct light from a static cylindrical body in burnished brass. Its compact geometry is distinguished by a fully knurled surface that introduces visual rhythm. Also available in a Flat version with a reduced thickness canopy, it ensures discreet ceiling integration, making it suitable even for contract settings. Beak is also available in floor, reading, picture, table, suspension, wall versions and another ceiling model.

PRODUCTS DETAILS	FUNCTION	CEILING
	LOCATION	INTERIOR
	LIGHT EMISSION	DOWNLIGHT
	LIGHT SOURCE	COB LED CLU703 6W 724lm 700mA 9V CRI90 2700°K
	ENERGY EFFICIENCY	F
	RATED VOLTAGE	110 - 120 V / 220 - 240 V
	FREQUENCY	50 - 60Hz
	SUPPLY	BEAK CEILING POINT TERMINAL BLOCK BEAK CEILING POINT FLAT REMOTE TERMINAL BLOCK
	LENS SPOT BEAM	18° - 36° - 60°
	BEAK CEILING POINT: DALI or TRIAC dimming kit available upon request	
	BEAK CEILING POINT FLAT: DALI or TRIAC remote dimming kit available upon request	
	Switch on/off and Dimmable Switch to be combined upon request	

CERTIFICATION	UL / CE   IP20
---------------	--

MATERIALS	STRUCTURE	
	M11	LIGHT BURNISHED BRASS
	M12	DARK BURNISHED BRASS

PACKAGE	QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
	1 x BOX	15 x 15 x H 30 cm (5"9 x 5"9 x 11"8)	0,5 kg	1 kg	0,006 m³

DIMENSIONS	BEAK CEILING POINT STANDARD	NORTH AMERICAN WALL PLATE
		
	BEAK CEILING POINT FLAT STANDARD	NORTH AMERICAN WALL PLATE
	